

econ floor

POLSKA SP. Z O.O.

PRODUCT DATA SHEET

-EN-

COLLECTION BIG SIZE 70

TECHNICAL DATA
BIG SIZE 70

Product	SPC Rigid Vinyl floor, Big Size 70
Thickness	7.0 mm
Wear layer	0.55 mm
Clicking system	Pushdown Click-system
IXPE-Aluminium underlay	1.7 mm (incl. 0.2 mm aluminium foil)

Features	Waterproof, Wear-resistant, Anti-slip, Rot-, Fire-, Sound-, Mold-proof
Measurements	1830 x 230 mm
Surface treatment	Ceramic & UV coated, EIR (Embossed in register), Hand-brushed wood
Advantages	Easy click-system to install, Labor costs saving, Strong stability, Eco-friendly
Density	2.0g/cm3

Technical data	Test method	Result
Abrasion resistance	EN 660-2	42
Slip resistance	EN 13893/DIN 51130	R11 Class
Color fastness	EN ISO 105-B02	≥6
Castor chair resistance	ISO TR4918	Passed
Chemical resistance	EN ISO 26987	Excellent
Flame retardency	EN 13501-01	Bfl-s1
Toxicity	EN 71	Non toxic
Dimensional stability	EN434	< 0.06%
Castor chair effect	EN425	Good
Underfloor heating	EN12524	Suitable
Antibacterial properties	EN846	Very good
Peel strength	EN	100N/5cm
Load test	EN433	0.03
Thermal resistance	---	0.026 m^2·K/W
Thermal conductivity	---	0, 1001 W / m.K
VOC	EN 16516	A+